



A|LVT URBAN WOODS Luxury Glue Down

Technical Info		
Style Name	AJLVT Urban Woods	
Style Number	APLD	
Application	Residential/Light Commercial/Commercial Vinyl Tile	
Class	ASTM F1700 Class III Printed Film Vinyl Plank Type B (Embossed)	
Standard wear layers*	8mil (0.2mm); 12mil (0.3mm); 20mil (0.5mm) ; 28mil (0.7mm)	
Standard thicknesses (overall)*	2.0mm; 2.5mm; 3.0mm	
Standard formats*	6" x 48" nominal (157mm x 1242mm); 10" x 60" nominal (253mm x 1530mm)	
Finish	Urethane	
Installation	Glue down	

	6" x 48" (157mm x 1242mm)			10" x 60" (253mm x 1530mm)		
Packaging	2.0mm	2.5mm	3.0mm	2.0mm	2.5mm	3.0mm
Ft ² per carton	41.67 SF/CTN	33.58 SF/CTN	27.92 SF/CTN	41.67 SF/CTN	33.33 SF/CTN	33.33 SF/CTN
Pieces per carton	10 PCS/CTN	16 PCS/CTN	14 PCS/CTN	10 PCS/CTN	8 PCS/CTN	8 PCS/CTN

Performance Data		
Resilient Floor Covering Institute	FloorScore® certified	
ASTM F970 Static Load Limit	Passes; ≥250 psi	
ASTM C1028 Coefficient of Friction	Dry .81 / Wet .80	
ASTM F2199 Dimensional Stability	Passes; no greater than .51mm/305mm	
ASTM F1914 Residual Indent	Passes; average less than 8%	
ASTM F925 Resistance to Chemicals	Passes; no change	
ASTM F2055 Squareness	Passes; maximum deviation of .25mm	
ASTM F2055 Size & Tolerance	Passes; no greater than .4mm/305mm	
ASTM F1514 Resistance to Heat	Passes; Average ΔE* _{ab} ≤ 8.0	
NALFA Castor Chair Resistance	No visible damage – 25,000 revolutions	
ISO 16000 parts -3, -6, -9, -11	A+ VOC Emissions Class	
ISO 9000 Quality Management	Production conforms to ISO 9001:2008	

Warranty Information	8mil	12mil	20mil
Wear Layer Warranty, Residential	10 year	15 year	25 year
Wear Layer Warranty, Commercial	N/A	5 year (limited/light)	10 year (limited)
Supplemental Warranty	Ardex SystemOne™ up to 10 years		

Contact Information	
Email	info@aproductUS.com
Phone	(888) 203-0054









